



**Service:**

For steam, air, water, oil and other fluids.

Operating Air Pressure: 3-5 kg/cm<sup>2</sup>G

Remark:

Up 4" are double acting cylinder actuator.

Connection Rating JIS 10K.

**PARTS**

Body		FC 250	SCS 13 (SUS 304)
Parts Name			
1	Handle Wheel	FC - 250	FC - 250
2	Cylinder	STKM 13C	STKM 13C
3	Actuator Stem	SS 41	SS 41
4	Yoke	FC - 250	FC - 250
5	V-Packing	Teflon	Teflon
6	Bonnet	FC - 250	SCS 13
7	Plug Stem	SUS 304	SUS 304
8	Plug	SUS 304	SCS 304
9	Sealing Ring	Teflon	Teflon
10	Body	FC - 250	SCS 13
11	Bottom Flange	FC - 250	SCS 13

Valve size		L	H1	H2	H	D
mm	inch					
20	3/4	160	90	320	410	120
25	1	160	90	320	410	120
32	1 1/4	160	90	320	410	120
40	1 1/2	190 200	100	400	500	150
50	2	210 220	108	412	520	150
65	2 1/2	230	120	440	560	175
80	3	260	130	450	580	175
100	4	280	145	515	660	205